

Traka Touch Pro M

Specifications



Traka's electronic key management systems secure, manage and audit the use of every key in your business.

The Traka Touch Pro range is built to last, built for simplicity, built for flexibility, and built with sustainability in mind.

Traka Touch Pro M key cabinets can manage 20 keys (or 40 keys using double-density strips) and are ideal for organizations with smaller amounts of keys to control.



General features

- Keys are readily available 24/7
- Access by authorized users only
- Full audit trail of all users and key transactions
- Securely store and manage up to 20 keys (or up to 40 keys using double-density strips)
- 7" capacitive touch screen for accurate input
- Easy access via a wide range of identification methods
- Battery backup with no data loss in the event of long term power failure

Standalone features

- Operates entirely independently of your IT system with no network, PC or external connection required
- Standalone 'plug and play' system
- USB port for import/export of reports via memory stick
- Automatic data backup to removable SD card

Network features

- Full network capability and management through TrakaWEB
- Centralized administration and reporting
- Browser-based for remote administration
- Integrate with existing access control and third-party systems to provide centralized control and visibility

Specifications

Mechanical data	
Height:	395.5 mm / 15.6 in
Width:	846 mm / 33.31 in
Depth:	160 mm / 6.3 in
Weight:	22.4 kg / 49.4 lbs

Material data	
Cabinet material:	Aluminium
Color:	RAL7021 (black grey)
Door material:	Clear polycarbonate or solid metal

Electrical data	
Power supply:	Input: 100-240V AC; Output: 15V DC
Battery backup:	DC12V 7Ah (H) 97.5 mm x (W) 65 mm x (L) 151 mm / (H) 3.84 in x (W) 2.56 in x (L) 5.94in
Power consumption:	35W max, typical 7W idle

Key positioning data	
Key positions:	10 - 20 (or up to 40 using double-density strips)
Receptor strip support:	Locking and non-locking strips, with or without button release. Tri-color LEDs to guide users.

Installation data	
Mounting:	Not suitable for freestanding applications. Must be securely fixed to a load bearing wall.

Environmental data	
Operating temp:	Ambient, for indoor use only (-5°C to +40°C / +23°F to +104°F at 95% non-condensing relative humidity)

Network & connectivity data	
Users per system:	Up to 40,000 ¹
Communications:	Ethernet (TCP/IP) 10/100 MB
Reader interface:	Clock/data, Wiegand, Serial (RS232/TTL), PIN only, OSDP Readers (RS485) with or without encryption
Alarm interface:	3x1A/24V dry contact relay contacts for connecting to alarms, access control or CCTV systems

¹When using biometric readers each system can support up to 3000 users

Conformity & standards data	
Product compliance	
UK	UKCA
EU	CE
USA	FCC
USA	MET NRTL
Canada	ICES
Canada	MET NRTL
Business compliance	
Quality:	ISO9001
Environmental:	ISO14001
Information Security:	ISO27001

For more information on Traka and the benefits of intelligent lockers, please visit traka.com

traka.com

The ASSA ABLOY Group is the global leader in access solutions. Every day we help people feel safe, secure and experience a more open world.