

# Traka Touch Pro V

## Specifications

traka  
ASSA ABLOY

Traka's intelligent key management solutions secure, manage and audit the use of every key in your business.

The Traka Touch Pro V is an electronic key management system that can store up to 5 sets of keys.

Its compact and space-saving design makes this key cabinet ideal for use across multiple locations where space is at a premium.



### General features

- Keys are readily available 24/7
- Access by authorized users only
- Full audit trail of all users and key transactions
- Securely store and manage 5 keys
- 7" capacitive touch screen for accurate input
- Easy access via a wide range of identification methods
- Battery backup with no data loss in the event of long term power failure

### Standalone features

- Operates entirely independently of your IT system with no network, PC or external connection required
- Standalone 'plug and play' system
- USB port for import/export of reports via memory stick
- Automatic data backup to removable SD card

### Network features

- Full network capability and management through TrakaWEB
- Centralized administration and reporting
- Browser-based for remote administration
- Integrate with existing access control and third-party systems to provide centralized control and visibility

## Specifications

| Mechanical data |                    |
|-----------------|--------------------|
| Height:         | 472 mm / 18.6 in   |
| Width:          | 250 mm / 9.8 in    |
| Depth:          | 173 mm / 6.8 in    |
| Weight:         | 11.8 kg / 26.0 lbs |

| Material data     |                                    |
|-------------------|------------------------------------|
| Cabinet material: | Aluminium                          |
| Color:            | RAL7021 (black grey)               |
| Door material:    | Clear polycarbonate or solid metal |

| Electrical data    |                                                                                         |
|--------------------|-----------------------------------------------------------------------------------------|
| Power supply:      | Input: 100-240V AC; Output: 15V DC                                                      |
| Battery backup:    | DC12V 7Ah (H) 97.5 mm x (W) 65 mm x (L) 151 mm / (H) 3.84 in x (W) 2.56 in x (L) 5.94in |
| Power consumption: | 35W max, typical 7W idle                                                                |

| Key positioning data    |                                                                                                |
|-------------------------|------------------------------------------------------------------------------------------------|
| Key positions:          | 5                                                                                              |
| Receptor strip support: | Locking and non-locking strips, with or without button release. Tri-color LEDs to guide users. |

| Installation data |                                                                                            |
|-------------------|--------------------------------------------------------------------------------------------|
| Mounting:         | Not suitable for freestanding applications. Must be securely fixed to a load bearing wall. |

| Environmental data |                                                                                                        |
|--------------------|--------------------------------------------------------------------------------------------------------|
| Operating temp:    | Ambient, for indoor use only (-5°C to +40°C / +23°F to +104°F at 95% non-condensing relative humidity) |

| Network & connectivity data |                                                                                                    |
|-----------------------------|----------------------------------------------------------------------------------------------------|
| Users per system:           | Up to 40,000 <sup>1</sup>                                                                          |
| Communications:             | Ethernet (TCP/IP) 10/100 MB                                                                        |
| Reader interface:           | Clock/data, Wiegand, Serial (RS232/TTL), PIN only, OSDP Readers (RS485) with or without encryption |
| Alarm interface:            | 3x1A/24V dry contact relay contacts for connecting to alarms, access control or CCTV systems       |

<sup>1</sup>When using biometric readers each system can support up to 3000 users

| Conformity & standards data |          |
|-----------------------------|----------|
| Product compliance          |          |
| UK                          | UKCA     |
| EU                          | CE       |
| USA                         | FCC      |
| USA                         | MET NRTL |
| Canada                      | ICES     |
| Canada                      | MET NRTL |
| Business compliance         |          |
| Quality:                    | ISO9001  |
| Environmental:              | ISO14001 |
| Information Security:       | ISO27001 |

For more information on Traka and the benefits of intelligent lockers, please visit [traka.com](https://traka.com)

[traka.com](https://traka.com)

The ASSA ABLOY Group is the global leader in access solutions. Every day we help people feel safe, secure and experience a more open world.

PS-TTPV-EN V3 US